manthorpe building products

Product Information Sheet

Large Format Tile Ventilator Range - System Overview

CODE GTV


Description

The Manthorpe range of large format in-line tile ventilators are designed to provide roof space ventilation or act as an outlet for ventilation ducting through 17" x 13" concrete roof tile coverings. The range of six profiles are universal in design and are compatible with all major UK and Irish tile makes.

The tortured path and in line design gives a discreet, weather proof 10,000 mm² airflow path through the roof with the recommended 4mm spaced grill openings to prevent the entry of debris and large nesting insects.

Available in a range of five* colours to suit most tile types, the vents are quick and easy to install, taking the place of a single tile with no need to cut the battens.

When used for mechanical extracion or soil stack / vent pipe termination; the GTV-AD Flexi Pipe Adaptor and GRPA Flexible Pipe range should be used. For detailed fitting instructions see MBP-0875, and for mechanical extraction fitting details see MBP-8297.



Materials - Top	terials - Top PVC	
Base	Base Polypropylene	
Colours	Terracotta, Grey, Brown, Antique Red & Anthracite Black	
Free Airflow	10,000 mm² per unit	

^{*} Anthracite Black colour only available with GTV-NP, GTV-FE and GTV-TE vents

	MANTHORPE BUILDING PRODUCTS LTD MANTHORPE HOUSE	TEL: 01773 303 000 FAX: 01773 303 300	DRN B.H. Date 19.06.19	DRG No	Issue
BRITTAIN DRIVE CODNOR GATE BUSINESS PARK RIPLEY		mbp.care@manthorpebp.co.uk of co	The company maintains a policy of continuous development of its product range and reserves the	MBP 8292	D
		www.manthorpebp.co.uk	right to amend the specification without notice.		(1 of 2)

manthorpe building products

Product Information Sheet


Large Format Tile Ventilator Range - System Overview


CODE GTV

Features

- In-line and discreet low profile design.
- 4mm louvred flyscreen grill.
- Integral sidelock clip to ensure secure fit.
- Range of profiles and colours available.
- Profiles suit all top tile manufacturers.
- Fully independently wind tunnel tested.
- Base outlet feeds directly into roof space.
- Adaptor available for mechanical extraction.
- Suitable for use down to a 20° roof pitch.

Vent Spacings		
To achieve: 25,000mm²/M	Place vents at 400mm centres	
To achieve: 10,000mm²/M	Place vents at 1 metre centres	
To achieve: 5,000mm²/M	Place vents at 2 metre centres	





Flexi Pipe Adaptor **GTV-AD**

Available for use with mechanical extraction and vent pipe termination. Connects the tile vents to GRPA Flexi Pipes and other 4" diamter ducting systems

References

BSI: BS 5250:2011 Control of Condensation in Building

BSI: BS 5534:2014 Code of Practice for Slate and Tiling

BSI: BS 490:2004 Concrete tiles and fittings for roof covering

BRE: prEN 15601

Building Regulations 2010

NHBC: Good Craftsmanship Guides

MANTHORPE BUILDING PRODUCTS LTD MANTHORPE HOUSE **BRITTAIN DRIVE**

CODNOR GATE BUSINESS PARK **RIPLEY**

DERBYSHIRE

DE5 3ND

TEL: 01773 303 000 FAX: 01773 303 300 EMAIL:

mbp.care@manthorpebp.co.uk

WEB

www.manthorpebp.co.uk

DRN B.H. Date 19.06.19

The company maintains a policy of continuous development of its product range and reserves the right to amend the specification without notice.

DRG No

Issue

MBP 8292



(2 of 2)