
Ulti-Line Slate Vents Fixing Instructions



600 x 300mm Installation



Decide position where vent is to be installed, cut and mark membrane and cut Slates 125mm width and 230mm from top

Fold Envelope section of the Membrane over the top batten and secure into position



Slide in Vent in Black or Grey, using Copper Rivet for appearance. If being used for extraction also select Flexipipe **ULTI3FP**



Fix slate either side of Vent and cut down slate over the top of the Vent, ensuring that side slates lap over the Vent



Start to lay slate around the vent ensure that these are nailed in line with the Slate manufacturers



Complete the roof and when finished you will have the Ulti-Line Slate Vent installation completed

Cut out for batten is centre of batten, then 250mm split equally each side Cut out is Headlap less 10mm and Sidelap less 5mm

Complete the roof and when finished you will have the Ulti-Line Slate Vent installation completed



All products are covered by our 15 year Durability Warranty terms and conditions can be found on our website.



All plastic products are made in UK.

500 x 250mm or less Installation





Cut Slates so that Slate Vent Spigot can fit working on width at Side Lap less 5mm and Gauge less 10mm

Decide position of Vent, mark

out lap line on slate and mark

to be removed. Fix batten for

nail fixing of the Vent and cut

Membrane

of 2nd batten section that needs



4



Cut and dress slates into the sides and top of the Vent, ensuring that side slates lap

over the Vent

Lay next course of Slate and cut

around the top of the grill so that

gauge is maintained

recommended nail size

ulti-mate-roofing.co.uk